

Spartan™ 2m podwójna linka bezpieczeństwa

Spartan™ 2m podwójna linka bezpieczeństwa / FAR0307



OPIS

Linki Spartan™ są produkowane z płaskiej taśmy 33 mm ze stalowymi karabinkami. W komplecie karabinek i 2 haki do rusztowania.

OPCJE

Spartan™ 2m podwójna linka bezpieczeństwa (FAR0307)

NORMY BEZPIECZEŃSTWA

EN 355

SPECYFIKACJE

Wskaźnik upadku
Tak

Długość
2m

Materiał
Taśma poliestrowa o szerokości 30mm z pętlami na obu końcach

Amortyzator
Zewnętrzna

TESTOWANE KRAWĘDZIOWO
Nie

Końce lin
X

Rękaw ochronny liny
Nie



Waga Produktu
1700g

Dostarczane z
1 karabinek z zamknięciem śrubowym ze stali stopowej. Otwarcie 18mm. Zgodne z normą EN362 klasa B i M. 2 Haki do rusztowania ze stali stopowej. Otwarcie 50mm Spełnia wymagania normy EN362 klasa T.

PLIKI DO POBRANIA

 [Zbiór zdjęć \(ZIP\)](#)

 [doc-far0307-far0318.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsspsafety.com / Web: www.jsspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 27 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

