

# TECHNICAL SPECIFICATION



## EVO®5 Olympus® Mid Peak Slip Ratchet Vented

Yellow / AKF160-000-200



### DESCRIPTION

The EVO®5 Olympus® safety helmet combines a super strong ABS shell designed for superior protection with the comfort benefits of the Evolution® 3D-Adjustment harness system.

EVO®5 Olympus® Industrial safety helmet passes all relevant industrial international standards.

### OPTIONS

Blue (AKF160-000-500)

Red (AKF160-000-600)

White (AKF160-000-100)

**Yellow (AKF160-000-200)**

### SAFETY STANDARDS

EN 397 • ANSI/ISEA Z89.1 Type I • AS/NZS 1801 • CSA Z94.1



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.






















Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 13 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

|  |   |   |  |
|--|---|---|--|
|    | Peak<br>Mid   |  | Impact Resistance<br>50 Joules                               |
|    | Lateral Deformation<br>Yes  |  | Resistance to Molten Metals and Hot Solids (optional)<br>Yes |
|    | Maximum Temperature<br>+50°                                       |  | Minimum Temperature<br>-40°                                  |
|    | ABS Shell<br>Yes  |  | Recyclable<br>Shell  |
|    | Textile<br>Harness  |  | Depth Adjustment<br>3D Harness                               |
|    | Slip Ratchet<br>Slip  |  | Ventilation<br>Yes   |
|    | Reflective Option<br>Optional                                     |  | Integrated Eyewear<br>Optional                               |
|    | ID card holder<br>Optional  |  | BSI Kitemark<br>Yes  |
|    | Optional 2 point chinstrap (EN397 & EN 812 compliant)<br>Optional |  | Optional 4 point chinstrap (EN397 Compliant)<br>Optional     |
|    | JSPCheck<br>Yes   |  | Product Weight<br>372g                                       |
|  | Size<br>53-64cm   |   |  |

## FEATURES



### Tough ABS Shell

The EVO@5 safety helmet features an extremely robust ABS shell designed for superior protection. It features a distinctive five stripe design and the JSP Shield.



### Textile Harness

A 6-point textile cradle harness system & Chamlon™ cotton sweatband offer unrivalled comfort.



### CR2 Reflective

Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility / reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



### JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



### Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. The Revolution® wheel ratchet makes it simple to tighten to the perfect fit.



### 3D Adjustment

The textile harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.



### Accessories

A universal attachment slot enables firm fitting of a range of Surefit™ safety visors and ear defenders. EVOSpec® Integrated eyewear is also available.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 13 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



## LOGO

- ☒ Front
- ☒ Back
- ☒ Sides

## RANGE



## DOWNLOADS

- [Image Pack \(ZIP\)](#)
- [doc-invincible\\_evo5.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 13 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

