TECHNICAL SPECIFICATION

EVO®5 Olympus® Mid Peak Slip Ratchet Vented

Yellow / AKF160-000-200

DESCRIPTION

The EVO®5 Olympus® safety helmet combines a super strong ABS shell designed for superior protection with the comfort benefits of the Evolution® 3D-Adjustment harness system.

EVO®5 Olympus® Industrial safety helmet passes all relevant industrial international standards.

OPTIONS

Blue (AKF160-000-500)

Red (AKF160-000-600)

White (AKF160-000-100)

Yellow (AKF160-000-200)

SAFETY STANDARDS

EN 397 • ANSI/ISEA Z89.1 • AS/NZS 1801 • CSA Z94.1

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Peak
Mid

Lateral Deformation
Yes

Maximum Temperature
+50

ABS Shell
Yes

Textile
Harness

Slip Ratchet
Slip

Reflective Option
Optional

ID card holder
Optional

Optional 2 point chinstrap (EN397 & EN 812 compliant)
Optional

JSPCheck
Yes

Size
53-64cm

Impact Resistance
50 Joules

Resistance to Molten Metals and Hot Solids Helmets (optional)
Yes

Minimum Temperature
-40

Recyclable
Shell

Depth Adjustment
3D Harness

Ventilation
Yes

Integrated Eyewear
Optional

BSI Kitemark
Yes

Optional 4 point chinstrap (EN397 Compliant)
Optional

Product Weight
372g

FEATURES

Tough ABS Shell

The EVO®5 safety helmet features an extremely robust ABS shell designed for superior protection. It features a distinctive five stripe design and the JSP Shield.

Textile Harness

A 6-point textile cradle harness system & Chamlon™ cotton sweatband offer unrivalled comfort.

CR2 Reflective

Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility / reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.

JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.

Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. The Revolution® wheel ratchet makes it simple to tighten to the perfect fit.

3D Adjustment

The textile harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.

Accessories

A universal attachment slot enables firm fitting of a range of Surefit™ safety visors and ear defenders. EVOSpec® Integrated eyewear is also available.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Construction and Infrastructure	Mining, Aggregates and Quarrying
Oil, Gas and Chemical Companies	Rail and Tunnelling
Renewable, Wind and Solar Energy	Utilities Contractors

LOGO

- [x] Front
- [x] Back
- [x] Sides

RANGE

evo5® Mk5 evolution

DOWNLOADS

Image Pack (ZIP)

doc-invincible_evo5.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.