# TECHNICAL SPECIFICATION



# **EVOGuard®M Forestry Helmet Systems**

EVOGuard®M2 Forestry Helmet System / AKE24A-400-800



## DESCRIPTION

The EVOGuard®M Forestry browguard and helmet systems are innovative solutions to protect the wearer in a multitude of high risk working environments. All EVOGuard® visor components are fully compatible with a range of existing EVO® helmet models.

## OPTIONS

EVOGuard®M3 Forestry Helmet System (AKE24A-500-800) EVOGuard®M3 Forestry Helmet System - with Throat Cover & Sun Cape (AKE24E-200-800)

EVOGuard®M2 Forestry Helmet System (AKE24A-400-800)

#### SAFETY STANDARDS

EN 397 • EN 352-3 • EN 1731 • EN 166







Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com







#### **SPECIFICATIONS**



Peak

Standard



Lateral Deformation

Yes



Maximum Temperature

+50°C



ABS Shell

Yes



Depth Adjustment 3D Harness

3D Hairies



Ventilation

No



Integrated Eyewear

Fitted



Optional 2 point chinstrap (EN397 & EN 812 compliant)

Optional



Mounting

Helmet

Cup Material

ABS

Hygiene

Hygiene Kit



Increased Robustness resists a 22mm, 43g steel ball travelling at 5.1 metres per second. This is derived from the practical test which is to drop the ball (as stipulated) from a height of 1.3 metres.

S



Visor Length

18cm



BSI Kitemark

Yes



JSPCheck

Yes



Impact Resistance 50 Joules



Molten Metal

Yes



Minimum Temperature

-40°C



Textile Harness



Wheel Ratchet

Yes



Reflective Option

Fitted



ID card holder

Optional



Optional 4 point chinstrap (EN397 Compliant)

Fitted



SNR

31 dB

Adjustable Yes



Manufacturer's Trademark

JSP Dagger



Visible Light Transmittance (VLT)

70%

Material

ABS Frame and Woven Stainless Steel Mesh Visor



Recyclable

Yes



Product Weight

805g

# FEATURES



#### **Visor Range**

Two high performance complete forestry systems are available, enabling users to select the perfect visor for their task and price point.



#### **Dual Layer Protection**

The EVOGuard®M Forestry Helmet and Forestry Browguard Systems both feature a secondary layer of eye protection in the form of the integrated EVOSpec® polycarbonate retractable eyeshield.



#### **Balanced & Secure**

Fitted to a browguard or helmet, the selflubricating nylon hinges hold the visor securely in position even during extreme movement, whilst offering balanced, even weight distribution.



#### **Product Compatibility**

Designed to maximise compatibility with a broad range of JSP products, such as the Force®8 respirator with PressToCheck™, Springfit™





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.








#### **Supreme Comfort**

Features an easy to use Revolution® wheel ratchet and a 3D-Adjustment harness, which offers 1-2-3 point depth settings for increased adaptability to ensure a perfect, secure fit.





#### Coverage

EVOGuard® visors provide comprehensive facial coverage without limiting movement or vision.

#### **APPLICATIONS**

General guidance only and should not be considered a substitute for a full risk assessment

Agricultural

Forestry & Landscaping

LOGO

✓ Front





#### DOWNLOADS

















