SCHEDA TECNICA

Sottogola Elasticizzato Deluxe a 2 Punti con Mentoniera

Default / AHV000-500-000



DESCRIZIONE

Sottogola elastico con mentoniera, progettato per rompersi quando sottoposto a una trazione tra i 150N e 250N come da EN397

OPZIONI

Default (AHV000-500-000)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICHE

Tipo
Deluxe

RANGE

HEAD
ACCESSORIES

DOWNLOAD

Immagini Scaricabili (ZIP)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.