

Spartan[™] 2m Adjustable Single Fall Arrest Lanyard

Spartan[™] 2m Adjustable Fall Arrest Lanyard / FAR0310



DESCRIPTION

Webbing lanyard, adjustable from 1.45m to 2m, with integral shock absorber. The lanyard is made from 30mm wide polyester webbing with steel karabiner connector and steel scaffold hook, and features a fall indicator on the energy absorber.

OPTIONS

Spartan[™] 2m Adjustable Fall Arrest Lanyard (FAR0310)

SAFETY STANDARDS

EN 355



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Fall Indicator Yes

Material 30mm Wide Polyester Webbing With Textile Loops On Both Ends

Sharp Edge No

Protective Rope Sleeve No



Product Weight 1350g

Length Adjustable up to 2m

Shock Absorber External

Rope Ends X

Adjustment Device Manual Ring Type Adjuster Of Forged Alloy Steel

Delivered With

1 Screw Gate Connector In Alloy Steel. Gate Opening 18mm. Conforms to EN362 Class B & M. 1 Alloy Steel Scaffold Hook. Gate Opening 50mm. Conforms to EN362 Class T.

DOWNLOADS

Image Pack (ZIP)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.