

# TECHNISCHE SPEZIFIKATION



## 20m automatischer Seileinzug

20m automatischer Seileinzug / FAR0712



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jssafety.com](mailto:sales@jssafety.com) / Web: [www.jssafety.com](http://www.jssafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jssafety.com](mailto:copyright@jssafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 17 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.





## BESCHREIBUNG

Selbstaufrollende Rettungsleine aus 20 m Draht in einem robusten und langlebigen Kunststoffgehäuse, ausgestattet mit einem drehbaren Karabinerhaken aus Stahl und einem Aluminiumverbinder mit Schraubverschluss am Verankerungspunkt. Dieses Produkt verfügt

## OPTIONEN

20m automatischer Seileinzug (FAR0712)

## SICHERHEITSSTANDARDS

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 17 Sep 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.



außerdem über einen Griff zum bequemen Tragen.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 17 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



## SPEZIFIKATIONEN

Sturzindikator

Ja

Material

Verzinkter Stahldraht 4,5 Durchmesser

Scharfkantig

Nein

Bewertete Nennlast

140kg

Geliefert mit

1 drehbarer Stahlkarabinerhaken. Karabineröffnung 20mm. Entspricht EN362 Klasse T. 1 Aluminium-Schraubkarabiner am Verankerungspunkt. Karabineröffnung 22mm. Entspricht EN362 Klasse B

Länge

20m

Falldämpfer

Intern

Gehäuse

Robuster und langlebiger Kunststoff

Produktgewicht

6900g

## DOWNLOADS

 [Bilderordner \(ZIP\)](#)

 [doc-far0707-far0712.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 17 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

