

TECHNISCHE SPEZIFIKATION



20m Stahlseil - Höhengsicherungsgerät

20m Stahlseil - Höhengsicherungsgerät / FAR0712



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 25 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





BESCHREIBUNG

20 m lange selbstaufrollende Drahtseil-Rettungsleine in einem robusten und langlebigen Kunststoffgehäuse, ausgestattet mit einem drehbaren Karabinerhaken aus Stahl und einem Aluminiumverbinder mit Schraubverschluss am Verankerungspunkt. Dieses Produkt verfügt

OPTIONEN

20m Stahlseil - Höhensicherungsgerät (FAR0712)

SICHERHEITSSTANDARDS

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 25 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



außerdem über einen Griff zum bequemen Tragen.



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 25 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPEZIFIKATIONEN

Sturzindikator
Ja

Material
Verzinkter Stahldraht 4,5 Durchmesser

Scharfkantig
Nein



Bewertete Nennlast
140kg

Geliefert mit
1 drehbarer Stahlkarabinerhaken. Karabineröffnung
20mm. Entspricht EN362 Klasse T. 1 Aluminium-
Schraubkarabiner am Verankerungspunkt.
Karabineröffnung 22mm. Entspricht EN362 Klasse
B

Länge
20m

Falldämpfer
Intern

Gehäuse
Robuster und langlebiger Kunststoff



Produktgewicht
6900g

DOWNLOADS

 [Bilderordner \(ZIP\)](#)

 [doc-far0707-far0712.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 25 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

