

TECHNICAL SPECIFICATION



20m Wire Self-Retractable Lifeline

20m Wire Self-Retractable Lifeline / FAR0712



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 14 Dec 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.





DESCRIPTION

20m wire self-retractable lifeline in robust and durable plastic casing, equipped with steel swivel snap hook connector, and screw gate aluminium connector at anchorage point. This product also features a handle for convenient carrying.

OPTIONS

20m Wire Self-Retractable Lifeline (FAR0712)

SAFETY STANDARDS

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 14 Dec 2025 / Copyright 2018 - 2025, JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 14 Dec 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Fall Indicator
Yes

Length
20m

Material
Galvanised Steel Wire 4.5 Diameter

Shock Absorber
Internal

Sharp Edge
No

Casing
Robust and Durable Plastic



Rated Weight / Load
140kg



Product Weight
6900g

Delivered With
1 Steel Swivel Snap Hook. Gate Opening 20mm.
Conforms To EN362 Class T. 1 Screw Gate
Aluminium Connector At The Anchorage Point.
Gate Opening 22mm. Conforms To EN362 Class B

DOWNLOADS



[Image Pack \(ZIP\)](#)



[doc-far0707-far0712.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 14 Dec 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

