

ESPECIFICACIONES TÉCNICAS



Línea de vida autorretráctil de cable de acero de 20 m

Línea de vida autorretráctil de cable de acero de 20 m / FAR0712



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 25 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





DESCRIPCIÓN

Línea de vida auto-retráctil de cable de 20 m en carcasa de plástico robusta y duradera, equipada con conector de gancho de seguridad giratorio de acero y conector de aluminio de puerta de tornillo en el punto de anclaje. Este producto también incorpora un asa para facilitar

OPCIONES

Línea de vida autorretráctil de cable de acero de 20 m (FAR0712)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 25 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 25 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



ESPECIFICACIONES

Indicador de caída
Sí

Material
Alambre de acero galvanizado diámetro 4,5

Borde afilado



Peso/carga nominal
140kg

Se entrega con
1 gancho con cierre de seguridad giratorio de acero. Apertura del gatillo: 20 mm. Conforme a EN 362 Clase T. 1 conector de aluminio con cierre de rosca en el punto de anclaje. Apertura del gatillo: 22 mm. Conforme a EN362 Clase B

Longitud
20m

Absorbedor
Interno

Carcasa
Carcasa de plástico robusta y duradera



Peso del producto
6900g

DESCARGAR

 [Colección de imágenes \(ZIP\)](#)

 [doc-far0707-far0712.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 25 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

