

ESPECIFICACIONES TÉCNICAS



Línea de vida de cable auto-retráctil 20m

Línea de vida de cable auto-retráctil 20m / FAR0712



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 19 Dec 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.





DESCRIPCIÓN

Línea de vida auto-retráctil de cable de 20 m en carcasa de plástico robusta y duradera, equipada con conector de gancho de seguridad giratorio de acero y conector de aluminio de puerta de tornillo en el punto de anclaje. Este producto también cuenta con una asa para

OPCIONES

Línea de vida de cable auto-retráctil 20m (FAR0712)

NORMAS DE SEGURIDAD

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 19 Dec 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 19 Dec 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



ESPECIFICACIONES

Indicador de caída
Sí

Material
Alambre de acero galvanizado diámetro 4,5

Borde afilado

Peso/carga nominal
140kg

Se entrega con
1 Mosquetón giratorio de acero. Abertura 20mm.
Cumple con EN362 Clase T. 1 Conector de aluminio de puerta de tornillo en el punto de anclaje. Abertura 22mm. Conforme a EN362 Clase B

Longitud
20m

Absorbedor
Interno

Carcasa
Plástico robusto y duradero

Peso del producto
6900g

DESCARGAR

 [Colección de imágenes \(ZIP\)](#)

 [doc-far0707-far0712.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 19 Dec 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

